



## Electric Series Scissor Lifts

### 0407SE(1330SE)

Compliance with ISO/CE/ANSI/CSA/AS/CU-TR/KCS standards

#### Product Highlights

- Platform capacity up to 240kg(529lbs)
- Easily passes through standard doors and can access elevators
- Exclusive open chassis reduces daily maintenance time
- DC motor drive, giving a longer runtime

Standard features		
■ Maintenance-free battery	■ Automatic braking system	■ Drive at full height
■ Proportional control	■ Emergency lowering system	■ Forklift pocket and lifting eyes
■ Bumper rail	■ Emergency stop at both platform and ground controls	■ Electrophoresic paint technology
■ 4x2 drive	■ Fault diagnosis system	■ Foldable guardrail
■ Non-marking tyres	■ Tilt protection	
■ Integrated hand shield	■ Automatic pothole guard	
	■ Overload sensing system	
Optional features		
■ Overhead anti-collision device	■ Headlight	■ RCBO
■ AC power to platform		

Model	0407SE(1330SE)	
Dimension	Metric	US
Max Working Height	5.8m	19'
A Max Platform Height	3.8m	12'6"
B Max Horizontal Extension	0.6m	23.6"
C Length-Stowed	1.42m	4'8"
D Width-Stowed	0.76m	2'6"
Height - stowed	Rail Folded	1.67m 5'6"
	E Rail Unfolded	1.97m 6'6"
	Fixed Rail	1.97m 6'6"
F Wheelbase	1.11m	3'8"
Ground Clearance(Pothole Guard Stowed)	65mm	2.5"
Ground Clearance(Pothole Guard Deployed)	20mm	0.75"
Platform Dimensions(L×W×H)	1.34m×0.7m×1.1m	4'5"×2'4"×3'7"
Performance		
Platform Allowable Occupants(Indoor)	2 persons	
Platform capacity	240kg	529lbs
Lift Extension Capacity	100kg	220lbs
Drive Speed-Stowed	4km/h	2.5mph
Drive Speed-Raised	0.8km/h	0.5mph
Lift Time(Unloaded)	30s-33s	
Descent Time(Unloaded)	25s-30s	
Gradeability	25%	
Turning Radius(Inside/Outside)	0.3m/1.35m	12'/4'5"
Tilt Rating(Front to Back/Side to Side)	3°/1.5°	
Tyres-solid	230×80mm	9×3"
Power		
Batteries	12V×2/115Ah	
Power Source	24V DC	
Drive Mode	Motor, Rear wheel	
Charger Input	100-240V AC	
Charger Output	15A	
Hydraulic System Capacity	5L	1.1gal
Weight		
Weight(Indoor)	880kg	1,940lbs
Standards Compliance	ISO/CE/ANSI/CSA/AS/CU-TR	

