

Hydraulic Series Scissor Lifts

0408S/M(1530S/1532M)

0608S/M(1930S/1932M)

Compliance with ISO/CE/ANSI/CSA/AS/CU-TR/KCS standards

Product Highlights

Efficient and environmentally friendly

- Small turning radius, flexible operation in narrow spaces
- Standard forklift slot, for efficient equipment transportation
- Folding guardrails for easy transport

Reduced maintenance costs

- Double-door design for easy maintenance
- Troubleshooting for quick fault diagnosis
- Highly quality parts and components

More reliable performance

- Battery voltage early warning to ensure battery life
- Bumper rail protection
- The pothole protection reporting and horizontal protection system give peace of mind during operation

Standard features		
■ Maintenance-free battery	■ Automatic braking system	■ Drive at full height
■ Proportional control	■ Emergency lowering system	■ Forklift pocket and lifting eyes
■ Bumper rail	■ Emergency stop at both platform and ground controls	■ Electrophoresic painting technology
■ 4x2 drive	■ Fault diagnosis system	■ Foldable guardrail
■ Non-marking tyres	■ Tilt protection	
■ Integrated hand shield	■ Automatic pothole guard	
	■ Overload sensing system	
Optional features		
■ Overhead anti-collision device	■ Headlight	■ RCBO
■ AC power to platform		

Model	0408S/M(1530S/1532M)		0608S/M(1930S/1932M)		
	Metric	US	Metric	US	
Dimensions					
Max Working Height	6.6m	21'8"	7.8m	25'7"	
A Max Platform Height	4.6m	15'1"	5.8m	19'	
B Max Horizontal Extension	0.9m	3'	0.9m	3'	
C Length-Stowed	1.78m	5'10"	1.78m	5'10"	
D Width-Stowed	0.76m/0.81m	2'6"/2'8"	0.76m/0.81m	2'6"/2'8"	
Height	Stowed(Rail Folded)	1.84m	6'	1.86m	6'1"
	E Stowed (Rail Unfolded)	2.1m	6'11"	2.12m	6'11.5"
	Stowed(Fixed Rail)	2.1m	6'11"	2.12m	6'11.5"
	Stowed(Fixed Rail)	1.98m	6'6"	2m	6'7"
F Wheelbase	1.325m	4'4"	1.325m	4'4"	
Ground Clearance	70mm	2.8"	70mm	2.8"	
Platform Dimensions(LxWxH)	1.64m×0.76m×1.1m(5'5"×2'6"×3'7")		1.64m×0.76m×1.1m(5'5"×2'6"×3'7")		
Performance					
Platform Allowable Occupants (Indoor/Outdoor)	0408S(1530S): 2 persons/- 0408M(1532M): 2 persons/1 person		0608S(1930S): 2 persons/- 0608M(1932M): 2 persons/1 person		
Platform Capacity	280kg	617lbs	230kg	507lbs	
Drive Speed-Stowed	3km/h	1.86mph	3km/h	1.86mph	
Drive Speed-Raised	0.8km/h	0.5mph	0.8km/h	0.5mph	
Elevation Time(Unloaded)	15s-20s		15s-20s		
Descent Time(Unloaded)	28s-33s		25s-30s		
Gradeability	30%		25%		
Turning Radius(Inside/Outside)	0/1.49m	0/4'11"	0/1.49m	0/4'11"	
Tilt Rating(Front to Back/Side to Side)	3°/1.5°		3°/1.5°		
Tyres-solid	305×115mm	12"×4.5"	305×115mm	12"×4.5"	
Power					
Batteries	6V×4/225Ah		6V×4/225Ah		
Power Source	24V DC		24V DC		
Drive Mode	2WD, front wheel		2WD, front wheel		
Charger Input	100-240V AC		100-240V AC		
Charger Output	25A		25A		
Brake	2 rear wheel		2 rear wheel		
Hydraulic System Capacity	14L	3gal	14L	3gal	
Weight					
Weight	1,330kg	2,932lbs	1,526kg	3,365lbs	
	0408S(1530S) for indoor only		0608S(1930S) for indoor only		
Standards Compliance	ISO/CE/ANSI/CSA/AS/CU-TR/KCS				

