

Electric Series Scissor Lifts

0408SE/ME(1530SE/1532ME)
0608SE/ME(1930SE/1932ME)

Compliance with ISO/CE/ANSI/CSA/AS/CU-TR/KCS standards

Product Highlights

Efficient and environmentally friendly

- Higher work efficiency
- Environmental protection, zero emissions

Reduced maintenance costs

- Rapid, convenient transportation with two-way forklift slot
- Lower cost of ownership with highly versatile parts

More reliable performance

- Bumper rail protection

Standard features		
■ Maintenance-free battery	■ Automatic braking system	■ Drive at full height
■ Proportional control	■ Emergency lowering system	■ Forklift pocket and lifting eyes
■ Bumper rail	■ Emergency stop at both platform and ground controls	■ Electrophoresic paint technology
■ 4x2 drive	■ Fault diagnosis system	■ Foldable guardrail
■ Non-marking tyres	■ Tilt protection	
■ Integrated hand shield	■ Automatic pothole guard	
	■ Overload sensing system	
Optional features		
■ Overhead anti-collision device	■ Headlight	■ RCBO
■ AC power to platform		

Model	0408SE/ME (1530SE/1532ME)		0608SE/ ME (1930SE/1932ME)		
	Metric	US	Metric	US	
Dimensions					
Max Working Height	6.6m	21'8"	7.8m	25'7"	
A Max Platform Height	4.6m	15'1"	5.8m	19'	
B Max Horizontal Extension	0.9m	3'	0.9m	3'	
C Length-Stowed	1.8m	5'11"	1.8m	5'11"	
D Width-Stowed	0.79m/0.81m	2'7"/2'8"	0.79m/0.81m	2'7"/2'8"	
Height-Stowed	Rail Folded	1.87m	6'2"	1.88m	6'2"
	E Rail Unfolded	2.12m	6'11.5"	2.14m	7'
F Wheelbase	1.334m	4'4"	1.334m	4'4"	
Ground Clearance (Pothole Guard Stowed)	75mm	3"	75mm	3"	
Ground Clearance (Pothole Guard Deployed)	24mm	0.95"	24mm	0.95"	
Platform Dimensions(LxWxH)	1.64m×0.76m×1.1m (5'5"×2'6"×3'7")		1.64m×0.76m×1.1m (5'5"×2'6"×3'7")		
Performance					
Platform Allowable Occupants (Indoor/Outdoor)	0408SE(1530SE): 2 persons/- 0408ME(1532ME): 2 persons/1 person		0608SE(1930SE): 2 persons/- 0608ME(1932ME): 2 persons/1 person		
Platform Capacity	280kg	617lbs	230kg	507lbs	
Drive Speed-Stowed	4km/h	2.5mph	4km/h	2.5mph	
Drive Speed-Raised	0.8km/h	0.5mph	0.8km/h	0.5mph	
Elevation Time(Unloaded)	15s-20s		15s-20s		
Descent Time(Unloaded)	28s-33s		25s-30s		
Gradeability	25%		25%		
Turning Radius(Inside/Outside)	0/1.49m	0/4'11"	0/1.49m	0/4'11"	
Tilt Rating (Front to Back/Side to Side)	3°/1.5°		3°/1.5°		
Tyres-solid	323×100mm	12.7×4"	323×100mm	12.7×4"	
Power					
Batteries	6V×4/225Ah		6V×4/225Ah		
Power Source	24V DC		24V DC		
Drive Mode	Motor, front-wheel		Motor, front-wheel		
Charger Input	100-240V AC		100-240V AC		
Charger Output	30A		30A		
Hydraulic System Capacity	7L	1.5gal	7L	1.5gal	
Weight					
Weight	1,375kg	3,032lbs	1,575kg	3,473lbs	
	0408SE(1530SE) for indoor only		0608SE(1930SE) for indoor only		
Standards Compliance	ISO/CE/ANSI/CSA/AS/CU-TR/KCS				

